# **Used machines offer**

# VKS 4 Z - Front mounted sweeper

Offer number: UM1753082





Brand: Schmidt Mat.-Nr.: 270961-6 Year of manufacture: 2022

Serialnumber: VKS 4 Z-74-1-001

Running hours: 0 h
Condition: Class 5
Location: Germany

79837 St. Blasien

Price: On request

The front mounted sweeper is offered as stock unit with basic equipment in excellent condition. The attachment can be supplemented with additional equipment if necessary. The front mounted sweeper is ideally used on Unimog with a 1<sup>3</sup>/<sub>4</sub> inch PTO shaft.

Delivery ex works.

The equipment does not include: Mounting plate size 3 or 5, Lifting device size 3/5, Turning device, More options.

The attachment can be supplemented with the necessary additional equipment.

# Ga

### **Gallery**










14. 10	-				41
		<b>y</b> .	A		
	70		-		-
		s in mm / We VKS 22	VK5 24	VKS 26	VXS-4
Brush length	81	VKS 22 2200	VKS 24 2400	2600	2100
Grush longth Total width	61	2000 2372	2400 2572	2600	2100 2400
Grush length Total entith Travet wetth at 30" angle	81 62 80	VKS 22 2200 2372 2325	9400 9400 9672 2411	2600 2772 2498	2100 2400 2160 (at 267)
Grush length Total entith Travet wetth at 30" angle	61	2000 2372	2400 2572	2600	2100 2600 2160
Brush length Travel width 50° angle Brush disameter Height	81 62 80	VKS 22 2200 2372 2325	9400 9400 9672 2411	2600 2772 2498	2100 2400 2160 (at 267)
Brush longth Total redth Trities width at 30° angle Brush diameter Height Distance between bearing surface of the implement plate and brush centre	81 82 80 01 H1	900 2372 2325 800 976 1325	985 24 2400 2672 2411 600 976 1326	2600 2772 2498 600 6N6 1326	2100 2900 2160 (#267) 700 960 1148
(thrush length Total width Trisent width at 30° angle Bhush domitter Height Contains between bearing surface of the implement jobs and brush centre Report to the Mills	81 62 83 D1 H1	2000 22172 2325 800 976	2400 2400 2672 2411 600 976	2600 2772 2498 600 936	2100 2400 2160 (at 26") 700 660
Brush length Total width Total width at 30° angle Brush stamuter Height Contains between bearing surface of the implement joins and brush centre Reach to the face on the	81 82 80 01 H1	900 2372 2325 800 976 1325	985 24 2400 2672 2411 600 976 1326	2600 2772 2498 600 6N6 1326	2100 2900 2160 (#267) 700 960 1148
Brush length Total width Travel width at 20" angle Brush damater Travel width at 20" angle Distance between beloning surface of the implement politic and brush control Reuch to the fruit  People of centre of grantly  - version ,0"  - version ,0"	81 82 83 81 81 81 11	WG 22 2200 2272 2325 600 936 1326 2424 0 1000	985 24 2400 2672 2411 600 976 1326 2171 O 1050	2000 2772 2498 600 676 1326 2221 O 1060	2100 2400 2160 (#267) 300 980 1148 2010
Brush langth Total eventh Travel worth at 30° angle Brush data 30° angle Brush data 30° angle Brush data 30° angle Brush data 30° angle Brush da brush data 30° angle Brush da The Brush	81 82 83 81 81 81 11	WKS 22 2000 2222 2335 800 016 1328 2121 0 1026 V 1000	985.24 2400 2672 2411 600 516 1326 2171 0 1050 V 1030	2000 2772 2498 600 976 1326 2221 O 1080 V 1060	2100 2400 2160 (#1267) 700 680 1148 2010 0 1 200 V 1 200





# Equipment

Base attachment				
466115	Frount mounted sweeper VKS 4.2 Z-21			
Drive option				
718451	Cardan shaft 1 3/4"			
Option				
714826	Polypropylene (plastic) brush			



Andreas Schwald Head Special Clients and Key Accounts



© Aebi Schmidt Group www.aebi-schmidt.com

Aebi Schmidt Holding AG CH-8050 Zurich, Switzerland

All rights reserved. Technical data is subject to change. Illustrations are not binding. Errors and amendments excepted.

Document created on 15.12.2023







